



Woodward

froged brick in two distinct finishes - smooth and antique

DEPTH



65

Millimetres

FINISHES

Sm

Smooth

Ant

Antique



215 x 102.5mm

COLOURS



LYNDHURST SMOOTH *new*




LYNDHURST ANTIQUE




ASHBROOKE SMOOTH *new*




ASHBROOKE ANTIQUE *new*




HAMPTON SMOOTH *new*



HAMPTON ANTIQUE



TULLAMORE SMOOTH *new*



TULLAMORE ANTIQUE *new*



EDENMORE SMOOTH *new*



EDENMORE ANTIQUE *new*



NORTHUMBERLAND SMOOTH *new*



NORTHUMBERLAND ANTIQUE *new*



OXFORD SMOOTH *new*




OXFORD ANTIQUE *new*




CLARENDON SMOOTH *new*



CLARENDON ANTIQUE



BLUE SMOOTH *new*



WINDSOR SMOOTH *new*



Frost Resistant



Very Low Risk of Efflorescence



Very Low Water Absorption



Specials Available





Woodward

frogged brick in two distinct finishes - smooth and antique

DEPTH



65

Millimetres

FINISHES

Sm

Smooth

Ant

Antique

215 x
102.5mm

Woodward
technical information

SUSTAINABILITY

Energy Use
Water Used
Recyclable

100% renewable
100% rain water harvesting
100% of this product can be recycled

Manufacturing

Produced in the UK using responsibly sourced materials

Waste Wood + Plastic:
Carbon Footprint

100% recycled
We have a new state-of-the-art washing plant which enables AG to produce walling from 100% reclaimed waste aggregate. Please contact our Technical Specification Department if you are interested in specifying such a product.
BREEM
'A+' Rating – in accordance with the BRE Green Guide to Specification.

Information for a specific colour is available on request from our Technical Specification Department.

ADVICE + GUIDANCE

For advice and guidance on ordering, installation, good site practice, etc. visit our website:
professional.ag.uk.com/advice+guidance

For maintenance guidance and health and safety advice visit our website:
professional.ag.uk.com/maintenance

FEATURES + BENEFITS

- Available in two finishes - a smooth finish with crisp edges for a contemporary look; and an antique finish with rumbled edges for a more traditional look.
- Woodward bricks are frogged, so they are lighter and easier to handle than solid bricks.
- The frog creates an extra recess for the mortar, resulting in a stronger bond between bricks.
- Frogged bricks reduce the environmental impact as the indentation in the brick saves on materials, which also helps reduce the curing time of the bricks.

AG RECOMMENDATIONS

Frog

Woodward bricks should be laid with the frog facing upwards and completely filled with mortar.

Colour blending


Products should be mixed on site from a minimum of 3 packs to help reduce the effect of banding.

Mortar Ratio


Recommended ratio 6 : 1 or 5 : 1 (Sand : OPC).

EDGES

Woodward Brick is supplied with either crisp, clean edges (smooth finish) or distressed, round edges (antique finish).



Smooth



Antique

FINISHES

Woodward Brick comes in two finishes.

Smooth for a contemporary feel and a chic, modern look.

Antique with the rumbled, distressed finish of old reclaimed brick and all of the benefits of new brick.



Frost Resistant



Very Low Risk of Efflorescence



Very Low Water Absorption



Specials Available

SPECIFICATION REFERENCE: NBS PLUS: F10 BRICK/ BLOCK WALLING 215 CONCRETE FACING BRICKWORK BS EN 771-3: 2011





Woodward

froged brick in two distinct finishes - smooth and antique

DEPTH



65

Millimetres

FINISHES

Sm

Smooth

Ant

Antique

215 x
102.5mm

Woodward
stock information

STOCK INFORMATION

Product type	Length (mm)	Depth (mm)	Height (mm)	In Stock	Available Colours	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler	Packs per unit lorry
FACING BRICK	215	102.5	65	YES	Lyndhurst Smooth / Lyndhurst Antique / Ashbrooke Antique / Hampton Smooth / Hampton Antique / Clarendon Smooth / Clarendon Antique / Northumberland Smooth / Northumberland Antique / Edenmore Smooth / Edenmore Antique / Tullamore Antique	512	2.9	1.55	10	17
				MTO	Ashbrooke Smooth / Tullamore Smooth / Oxford Antique / Oxford Smooth / Blue Smooth / Windsor Smooth					

NB. In stock items requiring over 10,000 no. bricks are treated as made to order.

MTO - made to order (minimum order size 10,000 no. bricks).

Supplied without pallets (available on request).

All size dimensions are nominal.

TECHNICAL INFORMATION

MANUFACTURING STANDARD	BS EN 771-3: 2011+A1 : 2015 Attestation Level 2+ Category 1	THERMAL CONDUCTIVITY	1.56 W / m.K
COMPRESSIVE STRENGTH*	Min average 22 N/mm ²	INITIAL RATE OF ABSORPTION	0.42 Kg / m ² .m-1
WATER ABSORPTION (24HR)	6% max	BOND STRENGTH	0.15 N / mm ²
DURABILITY DESIGNATION	F2 Severe Exposure	REACTION TO FIRE	A1 Class
MEAN COEFFICIENT OF WATER ABSORPTION	4.4 g / (m ² .s)	TYPE OF MORTAR	Recommended ratio 6 : 1 or 5 : 1 Sand : OPC
MOISTURE MOVEMENT COEFFICIENT**	0.46 mm / m	WATER VAPOUR PERMEABILITY [u]	5 / 15u tabulated from EN 1745
ACTIVE SOLUBLE SALTS [SO3]	0.03%	PACK QUANTITY	512
SIZE TOLERANCE	BS EN 771-3: 2011 (T1) Category D2	PACK SIZE [APX. MM]	L 850 x D 850 x H 1100mm
GROSS DENSITY	2200 Kg / m ³	TYPICAL PACK WEIGHT	1600 Kg
		PACKAGING (FULL SHRINK BAG)	Unpalletted***

* Compressive strength in accordance with PD 6697 : 2010 and Eurocode 6.

** Determination of moisture movement and drying shrinkage carried out in accordance with BS EN 772-14:2001 (E)

*** Pallets are available on request.

MANUFACTURING

Woodward facing bricks are manufactured by using advanced manufacturing processes and natural materials. PLANT OF MANUFACTURE (POM): Made at our Fivemiletown Production Plant. All products are manufactured from natural materials and although we strive to provide consistency of colour, variation may occur in the manufacturing process - this applies to all concrete products within the industry.

CERTIFICATION

ISO 9001
ISO 14001
ISO 45001
CE Marking

Quality Management.
Environmental Management.
Occupational Health and Safety Management.
Download our Declaration of Performance (DOP) data at: www.ag.uk.com/cemarking

