

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/4

Fire Cement

Revision 6

Revision date 2020-08-10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Fire Cement
--------------	-------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
-------------	---

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Corr. 1A: H314;
--------------------------------------	----------------------

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label).

Fire Cement

Revision 6
Revision date 2020-08-10

2.2. Label elements

Precautionary Statement: Storage	P363 - Wash contaminated clothing before reuse.
	P405 - Store locked up.
	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Sodium Silicate		1344-09-8	215-687-4		10 - 20%	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Causes burns. Seek medical attention.
Skin contact	Causes burns. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	Corrosive. Burning produces irritating, toxic and obnoxious fumes.
--	--

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Avoid raising dust. Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Avoid raising dust. Sweep up. Transfer to suitable, labelled containers for disposal.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection

Fire Cement

Revision 6

Revision date 2020-08-10

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	Yellow
pH	14
Initial boiling point	100 °C

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation	Causes burns.
---------------------------	---------------

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

Fire Cement

Revision 6

Revision date 2020-08-10

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information**SECTION 16: Other information****Other information**

Revision	This document differs from the previous version in the following areas:. 8 - Respiratory protection. 14 - ADR/RID. 14 - IMDG. 14 - IATA.
-----------------	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--