



EXTERIOR



TEXTROL®

PENETRATING OIL FINISH FOR WOOD

Product description	<p>TEXTROL® is a penetrating oil finish that is designed to revitalize weather-beaten, dried-out decks and exterior wood. TEXTROL® restores the rich, warm appearance of natural wood and beautifies exterior wood. Developed to penetrate deep into the wood, it protects against damage caused by moisture and ultraviolet rays, and provides a mildew resistant finish that will not crack, peel or flake.</p> <p>When Textrol is first applied, the wood will darken to a rich matt colour, and then gradually lighten depending on the intensity of sun exposure.</p>
Properties	<ul style="list-style-type: none"> • Protects and enhances the beauty of exterior wood. • Long lasting natural looking. • Excellent penetration. • Non film building. No peeling. No flaking. • Mildew resistant finish. • Easy application. • Easy to maintain. No stripping. No sanding.
Basic uses	<ul style="list-style-type: none"> • For exterior use only. • Weathered exterior woods including Cedar, Redwood and Pressure-Treated Wood. • Horizontal and vertical surfaces such as decks, siding, shake roofs, fences, exterior wood furniture. • Do not use on hardboard, plywood, including T1-11 or over previously stained, varnished or painted wood. • Do not use on new wood.
Technical data	<p>Finish: matt Vehicle type: alkyd resins Solvent type: solvent Specific gravity: 0.875 Kg/l ±0.05 at 18°C Viscosity: Solid content: 31% ±2% by volume Flash point: > 64°C Shelf life: 2 years minimum in original unopened packaging Container size: 1L, 2.5L (Clear only), 5L, 20L, 200L Colour: Clear, Golden Oak, Medium Oak, Rustic Oak. Can be tinted with universal colourant (max 30ml/L). Dry time: 24 hours, depending on temperature and humidity Voc: eu limit value for this product (cat. A/f) 700 gr/L. (2010). This product contains max. 550 gr/L.</p>
Surface preparation	<p><u>New wood surfaces:</u></p> <ul style="list-style-type: none"> • New wood surfaces have a hard shiny surface known as mill glaze, that prevents maximum penetration and bonding of any finish. To properly prepare the surface for application, and minimise splitting, swelling, cupping and checking caused by exposure to the sun and rain, treat with Seasonite and allow wood to weather • Allow wood to weather (minimum 6-12 months) before applying Textrol. <p><u>Weathered wood surfaces:</u></p> <ul style="list-style-type: none"> • Surfaces must be clean, dry and free of dirt, grease, grime and mildew. • Treat mildew with a solution of 1 part bleach to 3 parts water. Scrub solution on to surface and allow to stand for 10-15 minutes; rinse thoroughly. • Clean weathered wood with NET-TROL® as per label directions, to remove the loose wood fibres, dirt and other surface contaminants. • If necessary sand surface after cleaning (80 grit paper). • After cleaning, allow wood to dry 2-3 days or until it has reached a moisture content of 18% or less before finishing. <p><u>Previously oiled surfaces:</u></p> <ul style="list-style-type: none"> • TEXTROL® may only be applied to bare wood surfaces or a weathered wood that was previously finished with TEXTROL®. All other oils or sealers must be completely and thoroughly removed with AQUANETT®* and NET-TROL®* per label directions, before applying TEXTROL®. • If necessary sand surface after cleaning and stripping (80 grit paper). • After cleaning, allow wood to dry 2-3 days or until it has reached a moisture content of 18% or less before finishing. <p><u>Previously coated surfaces:</u></p> <ul style="list-style-type: none"> • Textrol may only be applied to bare wood surfaces or a weathered wood surface that was previously finished with TEXTROL®. All previous coating must be completely and thoroughly removed with Dilunett and NET-TROL®* per label directions, before proceeding. • If necessary sand surface after cleaning and stripping (80 grit paper). • After cleaning, allow wood to dry 2-3 days or until it has reached a moisture content of 18% or less before finishing.

The information set out consists of purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

Application tools

- Brush: High quality, natural or synthetic bristle stain brush.
- Roller: medium pile.
- Spray: Air-Less sprayer .011 - .015 fluid tip/ 700-800 psi or less.
- Garden Sprayer.

Good application practice

- Before starting, test the colour choice on a small area. Allow to dry to determine final colour.
- Cover everything you do not wish to coat, including plants and shrubs.
- Apply between 5°C and 35°C. Do not apply in direct sunlight or to hot surfaces
- Do not apply if cold and/or wet weather is expected within 24-48 hours.
- Mix product thoroughly before and during application. Do not thin.
- Always work the entire length of a deck board or horizontal siding to a logical break, such as a window or door frame. Never stop application in the middle of wall.
- Vertical siding should be coated from top to bottom.
- Do not allow to dry between coats – apply TEXTROL® ‘wet on wet’
- After spray application, always back-brush or back-roll to improve penetration and uniformity of coverage.

Application

- Prepare surface as in « Surface Preparation »
 - Shake or stir can well before use
 - Apply 1st coat of Textrol and allow to penetrate into the wood (15-30 minutes).
 - Apply 2nd application and allow to penetrate for 15-30 minutes.
 - If required repeat this procedure until the wood is saturated i.e. will accept no more oil.
 - Do not allow Textrol to become Touch Dry or Dry between coats
 - Once the timber is saturated, brush out or wipe up any excess product that has not penetrated to avoid shiny spots.
- NOTE:** Textrol is not a surface coating, its place is in the wood not on the surface. Textrol protects by penetrating the wood, providing a rich matt finish.

Coverage

- Initial : 5m² per litre per 2 coats.
- Maintenance : 10m² – 12m² per litre.
- Coverage will vary depending on type, age and texture of wood.
- On recoats you will need about half the materials you used the first time.

Maintenance

DECKS & OTHER HORIZONTAL SURFACES

- Most decks & horizontal surfaces will only require a maintenance application of TEXTROL® every other year.
- A single application of Textrol every other year will be sufficient to refresh the natural beauty of the deck/ horizontal surface and to maintain protection.
- A periodic clean, between applications, with Net-trol to remove dirt and contamination will renew the appearance of the wood.

CLADDING & OTHER VERTICAL SURFACES

- Most cladding and vertical surfaces will only require touch up applications of TEXTROL®.
- When treated TEXTROL® areas turn grey, clean with Net-trol and apply a single application of Textrol to replace material which has weathered out.
- Areas retaining good colour do not need a maintenance application.
- Badly weathered areas may require 2 applications of TEXTROL® (apply the 2nd application as soon as the 1st has penetrated the wood).
- Surfaces with harsh exposures to the sun and weather will weather wear more quickly than other areas. If this happens, clean effected areas with NET-TROL®* and apply TEXTROL® as necessary, blending into areas which still have good colour. Areas retaining good colour do not need a maintenance application of TEXTROL®.

Clean-up

- Clean all tools and equipment with white sprits whilst still wet. If allowed to dry, remove with paint stripper.
- NOTE:** Any rags, steel wool etc soaked in TEXTROL® may spontaneously catch fire if improperly discarded. Rags, steel wool etc must be saturated with water after use or placed in a sealed, water filled metal container, before disposing with household waste

Storage

- Left over TEXTROL® should be transferred to a smaller, airtight, closed metal or glass container.
- Keep from freezing and high temperature.

Safety

Keep out of the reach of children. Do not breathe vapours. Avoid contact with skin. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

MSDS at www.owatrol.com

* same manufacturer.



OWATROL INTERNATIONAL SLU

08011 Barcelone - Espagne

T. +34 93 445 17 85 - F. +34 93 445 17 80

TEXTROL® is a trademark:



Find all our solutions:

www.owatrol.com