

Technical Data Sheet

Date of compilation: 13/08/2021

MOULD^X ANTI-MOULD STAIN BLOCK

DESCRIPTION

Isolation paint to protect against damp and efflorescence on mineral surfaces, for indoor and outdoor use.

MouldX Anti-Mould Stain Block isolates water, nicotine and soot stains. Prevents salt efflorescence on all mineral surfaces, such as concrete, lime and cement-based plaster, clay tiles, etc.

MouldX Anti-Mould Stain Block is not suitable for gypsum surfaces and gypsum boards, which are not permanently dry.



SURFACE PREPARATION

The surface can be moist, however, it must be firm and free of release agents. Remove efflorescence mechanically (brush) or using saltpetre remover.

APPLICATION

Stir MouldX Anti-Mould Stain Block well before use and apply using a brush or paint roller. Always apply two coats to achieve optimum isolation of the surface. Leave the first coat to dry for at least 8 hours before applying the second.

Do not mix MouldX Anti-Mould Stain Block with other paint systems however, can be thinned with max. 5 % white spirit to adjust its consistency. After the Stain Block has thoroughly dried, all cement-resistant paint systems can be used on it.

Do not use at surface or in rooms below + 5°C.

Clean tools immediately after use.

TECHNICAL INFORMATION

Property	Value
Components	Acrylic resin, aliphatic compounds, titanium dioxide, white cement and additives
Density	≈ 1,15 g/cm ³
Flash Point	≈ 43°C
Colour	White
Gloss level	Matt

Technical Data Sheet

Date of compilation: 13/08/2021

MOULDx ANTI-MOULd STAIN BLOCK

PACKAGING, CONSUMPTION & STORAGE

Supplied in 750ml Tin (6units/box).

Coverage: 150-200 ml/m² per coat.

Store in a cool place. Keep containers tightly sealed. Keep away from bare flames and ignition sources.

HEALTH & SAFETY

For more information and precautions for use refer to the safety data sheet.

NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail technical@arcbuildingproducts.ie. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.