

# Multi-Fix<sup>TM</sup> STELLA FIXING

**Highly effective universal anchor**  
for fixing heavy loads to plasterboard  
cavities and solid materials.

## TECHNICAL DATA

33 -  
48KG

Substrate	Plasterboard 12.5mm Thickness	Dense board 15mm Thickness	Double board 25mm Thickness
Anchor Type	Red	Red	Black
Anchor Length (mm)	49	49	59
Drill Hole Ø (mm)	10	10	10
Rec. Tensile Load (kN)	0.33	0.41	0.48
Max Rec. Load (kg)	33	41	48

**RED FIXING**  
**PERFECT FOR**  
**SINGLE BOARD**

**BLACK FIXING**  
**PERFECT FOR**  
**DOUBLE BOARD**



### BOX

Product Code	Screw Size (mm)	Plug Length (mm)	Board Thickness (mm)	MFT (mm)	Box Qty
<b>RED FIXING</b>					
STRED55	M5 x 55	49	3 - 18	15	25
STRED80	M5 x 80	49	3 - 18	40	25
<b>BLACK FIXING</b>					
STBLACK65	M5 x 65	59	18 - 30	12	25
STBLACK90	M5 x 90	59	18 - 30	38	25

TYPE - ANC

SUB TYPE - ANCO8

MFT = Max Fixture Thickness.



### PACK


Product Code	Screw Size (mm)	Plug Length (mm)	Board Thickness (mm)	MFT (mm)	Pack Qty
<b>RED FIXING</b>					
725374	M5 x 55	49	5 - 18	15	4
725146	M5 x 80	49	5 - 18	40	4
<b>BLACK FIXING</b>					
725012	M5 x 65	59	18 - 30	12	4
725973	M5 x 90	59	18 - 30	38	4

TYPE - PAK


SUB TYPE - PK011

MFT = Max Fixture Thickness.


## INSTALL IN JUST 3 EASY STEPS



**DRILL 10mm HOLE**  
**INTO SUBSTRATE**



**PLACE PLUG INTO**  
**HOLE UNTIL FLUSH**



**INSERT SCREW THROUGH THE FIXTURE.**  
**TIGHTEN & SECURE WITH A T25 DRIVER BIT**

