

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/4

Streetscape PS

Revision 7

Revision date 2020-01-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Streetscape PS
---------------------	----------------

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

Intended use

This product is intended for use as in the installations, bedding or grouting of paving for highways or pavements.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;
---	---

2.2. Label elements

Hazard pictograms



Signal Word

Danger

Hazard Statement

Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Eye Dam. 1: H318 - Causes serious eye damage.
STOT SE 3: H335 - May cause respiratory irritation.

Precautionary Statement: Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement: Response

P302+P352 - IF ON SKIN: Wash with plenty of water/ .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Streetscape PS

Revision 7

Revision date 2020-01-29

2.2. Label elements

Precautionary Statement: Storage Precautionary Statement: Disposal	P310 - Immediately call a POISON CENTER/doctor/ . P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.
	P501 - Dispose of contents/container to

2.3. Other hazards

Other hazards	P13 - Contains chromium (VI). May produce an allergic reaction. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
---------------	---

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Portland Cement		65997-15-1	266-043-4			Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;
Calcium Hydroxide		1305-62-0	215-137-3			Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H335;

Description

	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.
--	---

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Streetscape PS

Revision 7

Revision date 2020-01-29

6.1. Personal precautions, protective equipment and emergency procedures

Avoid raising dust. Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. This product must be stored in unopened manufacturers bags away from extremes of temperature in dry conditions. This product must be used before the use by date as shown on the bag. Use of this product after the use by date or incorrect storage may increase the risk of an allergic reaction from Chromium VI.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Calcium Hydroxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 5
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -
Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total inhalable dust: 10	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 15 min limit mg/m3 total respirable dust: -

8.2. Exposure controls**8.2.1. Appropriate engineering controls**

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Wear: Suitable respiratory equipment.

SECTION 9: Physical and chemical properties

Streetscape PS

Revision 7

Revision date 2020-01-29

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation	Irritating to eyes, respiratory system and skin.
---------------------------	--

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
	The product is not classified as Dangerous for the Environment.

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Text of Hazard Statements in Section 3	<p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Skin Sens. 1: H317 - May cause an allergic skin reaction.</p> <p>Eye Dam. 1: H318 - Causes serious eye damage.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p>
--	---

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--