

Never compromise on quality!



PLASTERERS PREGRIT Bonding Agent for Plaster

Description

A one part, ready-to-use internal plaster bonding agent with added aggregate to provide a key prior to plastering on smooth surfaces.

- Bonding Agent for smooth surfaces
- Contains sand/aggregate to provide plaster key
- Ready to use, one coat application
- Perfect for use on smooth substrates
- Pigmented yellow to identify treated areas
- Phthalate free formulation.

Uses

PLASTERERS PREGRIT should be used as a primer/ bonding aid prior to plastering on surfaces such as concrete, plaster and difficult, low or non-porous substrates. For internal use only, this product is not suitable for external applications..

Application

Thoroughly stir before use. Ensure all surfaces are clean, dry and free from any contaminants that may hinder adhesion, including any loose or flaking material. Ensure the background is sound and will support the weight of the plaster. Do not dilute. Simply apply one coat using a brush or roller and leave to dry for a minimum of 24 hours before plastering.

Note: cold or humid conditions will increase drying times. Do not use in temperatures below 5°C.

Limitations

- Do not use in areas where permanent dampness is likely.
- Do not use on new cement when cement has not fully cured. Do not use when the temperature is below 5°C.
- Do not use for external applications.

Storage Conditions

Store in cool, dry conditions in the original sealed container away from direct sunlight. Store between 5° C and 30° C.

Shelf Life

2 years when stored in cool, dry conditions.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Any spillages should be mopped up immediately with an inert absorbent material such as sand or sawdust.

Health & Safety

Safe in normal use, but the following is recommended. Wash splashes off skin or wear suitable gloves. If product enters eyes, wash immediately with cold clean water. Do not ingest. Keep out of reach of children . Some people are more sensitive to chemical products than others, if irritation occurs discontinue use.

Always follow the manufacturer's recommendations when using this product. It is the user's responsibility to determine suitability for use. Contact Technical Department if you are unsure. MSDS sheets are available on request for professional users or can be downloaded from www.bond-it.co.uk.

Coverage

Depending upon surface porosity aprox. 4-5m² / litre.

Specification Summary	
Specific Gravity	1.22g/ml
Viscosity	6,000 - 12,000 cP

Container Sizes:

Size:	5L	10L
Code:	BDPG10	BDPG05
Bar Code:	5060021368621	5060021368638

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN. Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: sales@bond-it.co.uk Website: www.bond-it.co.uk

BOND IT



V4 06/02/14