

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

CLP Felt Adhesive

Revision 3

Revision date 2020-08-10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	CLP Felt Adhesive
---------------------	-------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC9a] Coatings and paints, thinners, paint removers; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
--------------------	---

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	EUH066; Flam. Liq. 3: H226; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;
---	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	<p>EUH066 - Repeated exposure may cause skin dryness or cracking.</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>STOT SE 3: H336 - May cause drowsiness or dizziness.</p> <p>STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.</p> <p>Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.</p>
Precautionary Statement: Prevention	<p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 - Keep container tightly closed.</p> <p>P240 - Ground/bond container and receiving equipment.</p> <p>P241 - Use explosion-proof electrical/ventilating/lighting// equipment.</p> <p>P242 - Use only non-sparking tools.</p> <p>P243 - Take precautionary measures against static discharge.</p>

CLP Felt Adhesive

Revision 3

Revision date 2020-08-10

2.2. Label elements

Precautionary Statement: Response	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P370+P378 - In case of fire: Use to extinguish. P391 - Collect spillage.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.1. Substances

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Straight run kerosine - solvent naphtha (petroleum), medium aliph. Oxidised Bitumen	649-405-00-X	64742-88-7	265-191-7			Asp. Tox. 1: H304;
		64742-93-4	265-196-4			

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	. Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

CLP Felt Adhesive

Revision 3

Revision date 2020-08-10

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Oxidised Bitumen	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 2.9
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	Viscous liquid.
Colour	Black
Odour	Characteristic
Initial boiling point	> 153 °C
Flash point	> 39 °C
Upper Explosive Limit	8 %
Lower Explosive Limit	0.7 %
Autoignition temperature	> 200 °C
Solubility	Insoluble in water

9.2. Other information

CLP Felt Adhesive

Revision 3

Revision date 2020-08-10

9.2. Other information

Specific gravity	0.92 - 0.96 g/cm ³
------------------	-------------------------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

SECTION 12: Ecological information

12.1. Toxicity

	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

	UN1999
--	--------

14.2. UN proper shipping name

	TARS, LIQUID
--	--------------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

CLP Felt Adhesive

Revision 3

Revision date 2020-08-10

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 8 - Respiratory protection.
Text of Hazard Statements in Section 3	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--