



PF1

BOTAMENT®

Baustoffe für Profis 

Pavement Revive

- Concrete Paint
- Ideal for refreshing your concrete slabs and pavements

CERTIFIED



HIGH FROST AND
GRITTING SALT DURABILITY
Certified after: DIN EN 13687-1/ 1562



| 2,5 L | Outdoor | ≈15 m² | Dry ±1 Hour |



BOTAMENT PF1 Pavement Revive is a high-grade concrete coating to refresh concrete- and paving slabs in entrances and on pavements. It can refresh the color of old, deceased stones. Furthermore, it protects the surface from weathering.

Application areas

- Suitable surfaces: absorbent concrete stones (for example paving slabs) and mineral surfaces
- Unsuitable surfaces: Impregnated concrete surface, non-absorbent surfaces, washed concrete

Properties

- Cleaning – Applying – Done.
- High UV- and weather resistance.
- Preserves the natural structure of surfaces.

Surface preparation

- The surface must be absorbent, clean, dry and stable. Furthermore, it must be free from algae, moss, old coats of paint and layers of oil, fats, wax and impregnation which affect adhesion.
- If the surface has been cleaned with water (for example high-pressure cleaner) then the surface must be dry before application.

Application temperature (surface- & air temperature)	+12 °C
Consumption	~160 g/m ²
Coverage	Up to 15 m ² with one coating
Drying time	After ~1 hour almost dry After ~24 hours completely dry

Application

- Stir Botament PF1 Pavement Revive and if required put in appropriate tub. Apply the concrete coating thinly and evenly with a brush or a roller. Avoid pooling of material. If there are curbs, please paint before.
- If necessary, apply another coat.
- Clean tools with water after use.

Available in 3 colours

GREY

RED

ANTHRACITE

Tips

- BOTAMENT PF1 Pavement Revive can also be used with a suitable sprayer. In order to achieve an even result, the sprayed surfaces should be rolled again.

Information

- Make sure to always use the product with same batch numbers in order to avoid colour differences.
- Larger areas should be worked on in one application to ensure an even finish. Try to work along the joint..
- The coat only lasts partially on washed concrete, because it will just color the cement between the stones..
- Apply a trial coat on a non-visible area according to your environment.
- For further information please note our technical datasheet on www.botament.com or call our hotline.
- Safety datasheet is available on request for professional processors.
- EU- limit for this product (Kat. All/i): 140 g/l 2010. This product contains max. 140 g/l VOC.

Storage

Protect from frost – best product properties guaranteed for at least 24 months in original sealed packaging..

Disposal

Dispose emptied packages at recycling station.

BOTAMENT SYSTEMBAUSTOFF GmbH & Co. KG
Am Kruppwald 1 · D-46238 Bottrop · Tel. +49 20 41 10 19-0
info@botament.de · www.botament.de

MC Building Chemicals · Killycard · Castleblayney · Co. Monaghan.
+353 42 97515220
www.botament.com

2,5 L

BOTAMENT[®]

Baustoffe für Profis 

ANTHRACITE



BOTAMENT[®]

Baustoffe für Profis 

GREY

4 030905095227



BOTAMENT[®]

Baustoffe für Profis 

RED

4 030905 095210

