

# ALGAE REMOVER



Larsen Algae Remover is a clear liquid chemical algaecide and fungicide. It is a surface biocide for amateur and professional use against fungi, moulds and algae on internal and external surfaces such as render, masonry, concrete, tiles, tarmac and plaster. Larsen Algae Remover is suitable for application by brush or spray.

<section-header>

KILLS MOULD, FUNGI & ALGAE STOPS LICHEN INHIBITS NEW GROWTH HELPS PREVENT MOSS IDEAL FOR USE AS A FUNGICIDAL WALL SOLUTION PREVENTS IMMEDIATE RE-INFECTION ECONOMICAL TO USE USER FRIENDLY REMOVES RED & GREEN ALGAE IDEAL FOR USE ON RENDER, CONCRETE, MASONRY, BITMAC, PATHS AND PATIOS SAFE FOR PLANTS AND ANIMALS



Version: 01 Issued: Apr 24

# **TECHNICAL INFORMATION:**

PRODUCT INFORMATION	
FORM:	Clear Liquid
DENSITY:	1.0 kg/L
DILUTION:	Dilute 1L with 4L clean water
COVERAGE:	1L of concentrate makes 5L of diluted solution which will cover 25-90m <sup>2</sup> depending on method of application
APPROVAL:	This product is approved under the control of pesticides regulations for use as directed H.S.E. number: 6606 P.C.S. number: 102235
HAZARD INFORMATION:	Concentrated Liquid is Corrosive Diluted liquid is Irritant
PACKAGING:	1L, 2.5L and 5L packs
STORAGE CONDITIONS:	Store in sealed containers in dry conditions, protected from extremes of temperature
SHELF LIFE:	12 months in unopened manufacturer's packaging



## **DIRECTIONS FOR USE:**

### PREPARATION

Brush or hose clean any heavy build up of material prior to application. It is advisable to treat a trial area first prior to application. For best results, apply onto a dry substrate.

### **APPLICATION**

Dilute 1 part Algicide with 15.5 parts water. Apply liberally by brush, spray or watering can. Product does not require washing off. If the surface is to be washed again after use, leave product on the surface for a minimum of 1 hour before washing. Areas become typically become clean after 24-48 hours. Areas of heavy contamination may require a second treatment.

### RESTRICTIONS

Always take care when spraying and wear suitable protective equipment and take adequate precautions with regard to any overspray. Always test an inconspicuous area to ensure compatibility with substrate. Only the 1litre pack size is approved for amateur use.

### STATUTORY INFORMATION

### FOR USE ONLY BY PROFESSIONAL OPERATORS

The (COSHH) Control of Substances Hazardous to Health Regulations 2002 may apply to the use of this product at work. Engineering control of operator exposure must be used where reasonably practicable in addition to the following items of personal protective equipment. Wear suitable protective clothing, suitable gloves and eye/face protection.

AVOID EXCESS CONTAMINATION OF COVERALLS AND LAUNDER REGULARLY.

Do not breathe spray. Otherwise wear respiratory protective equipment. However, engineering controls may replace personal protective equipment if a COSHH assessment shows they provide an equal or higher standard of protection.

DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.

This material and its container must be disposed of in a safe way. When using, do not eat or smoke. Take off immediately all contaminated clothing. AFTER CONTACT WITH SKIN, WASH IMMEDIATELY with plenty of water and seek medical advice immediately. Wear suitable eye/face protection (when diluting). Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL THE SURFACES ARE DRY. COVER ALL WATER STORAGE TANKS before application. DO NOT USE NEAR DRAINS, PREVENT ANY SURFACE RUN-OFF FROM ENTERING DRAINS. REMOVE OR COVER ALL FISH TANKS AND BOWLS before application. This product contains substances which are known to be hazardous to the environment. Do not contaminate ground, waterbodies or watercourses with chemicals or used container.

The information and recommendations above are given in good faith based on our current knowledge and experience of the products when properly stored, handled and applied in accordance with current best practice, national standards and our recommendations. As we have no control over site conditions or methods of application, no liability can be derived from the contents of this information sheet, or from any written recommendations, or from any other advice offered. The user of the product is solely responsible for the product's suitability for the intended application and is recommended to test the suitability prior to use. We reserve the right to change the properties of our products without notice. All orders are sold subject to our current terms of sale and delivery. With the publication of this Technical Information Sheet all previous editions are no longer valid.

For further information consult our Technical Department BELFAST: 028 9077 4000 DUBLIN: 01 834 8255

www.larsenbuildingproducts.com