

GS12 is a self-adhesive fabric tape for the covering and reinforcing of joints in facings made of Botament BP Building boards.

PROPERTIES

- For covering joints in Botament BP Building boards
- High alkaline resistance
- High tear strength
- Easy to embed

AREAS OF APPLICATION

covering and reinforcing of

- joints in facings made of Botament BP Building boards

APPLICATION

- cut to fit GS12 using a carpet knife or scissors and fix the fabric tape onto the Botament BP Building boards
- rework BGS12 fabric tape with a thin filling layer made of Botament tile adhesive or GS4 smoothing filler

The fabric tape must not jut out at any point after sealing works have been finished.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Width	cm	10	
Weight	g/m	~ 55	
Tensile strength	N/5 cm	1,072	warp
		1,102	weft
base	Glasseidengewebe		
delivery form	20 m- roll (12 rolls/ box)		
Storage	Store in a cool, dry place!		

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by Botament's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300017281]