

TerraPave®

premium reconstituted granite aggregate flagstones



DEPTHS



40 | 50
70
Millimetres

FINISH



Ground



400 x
400mm




450 x
450mm



600 x
400mm

COLOURS


For 'Stock Information' on colours availability - see page 4.



RIMINI GROUND




VERONA GROUND




SORRENTO GROUND



GENOA GROUND



COMO GROUND



TUSCANY GROUND



MILANO GROUND



FLORENTO GROUND



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic when used as part of a bound system



Trolley Friendly



Abrasion Resistant





TerraPave®

premium reconstituted granite aggregate flagstones

DEPTHS



40 | 50
70
Millimetres

FINISH



Ground



STANDARDS + PERFORMANCE


Product Type	Premium reconstituted granite aggregate flagstones
Manufactured to	hEN 1339:2003
Surface Layer	Durable and hard wearing with a minimum surface layer of 8mm. Minimum cement content 380kg/m ³
Granite Content	Not less than 90% natural granite and quartz aggregate in surface layer
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Bending Strength	>5.0Mpa class 3. This pressure applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department
Slip / Skid Resistance	Ground finish: (PTV) >36 low potential for slip. Specific slip / skid resistance test results are available on request from our Technical Specification Department
Frost Resistance	Class 3 in accordance with hEN 1339:2003 Table 4.2
Abrasion Resistance	Class 4 in accordance with hEN 1339:2003 Table 6
Installed to	BS 7533-4:2006
NBS Plus	Q25 315

SUSTAINABILITY

BES 6001	Responsible Sourcing of Concrete Products (Rating: Very Good)
Energy Use	100% renewable
Water Used	90% recycled water
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK using responsibly sourced materials
Non-Primary Materials	52 – 60% (surface layer)
Waste Wood + Plastic	100% recycled
BREEAM	40 – 70mm: A Rating – according to the Green Guide to Specification 4th edition 2009. A+ Rating can be achieved when used in conjunction with a prepared recycled sub-base.

EDGES

TerraPave® Ground Supplied with a straight chamfer edge as standard. However a square edge can be specified for specific projects.



DIMENSIONAL TOLERANCES FOR WIDTH + DEPTH

Calibration before processing ensures strict compliance with hEN 1339:2003 tolerances and a low level of dimensional variance, delivering ease and accuracy of placement during installation, making them ideal for pedestals and much easier to lay on a well screeded bedding layer i.e. level and loose raked.

SPACER NIBS

No formed spacer.

FINISHES

TerraPave® Ground is created using a unique diamond grinding process for a superior finish.

TerraPave® colour blends have been carefully developed using shades from natural granite aggregates. No pigments are used, so you can be confident that the colours you choose won't fade over time.



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic when used as part of a bound system



Trolley Friendly



Abrasion Resistant



SPECIFICATION REFERENCE: NBS PLUS: Q25 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315; hEN: 1339:2003





TerraPave®

premium reconstituted granite aggregate flagstones

DEPTHS  40 50 70 Millimetres	FINISH  Ground	 400 x 400mm	 450 x 450mm	 600 x 400mm

AG RECOMMENDATIONS

Close Jointing

AG recommends a close joint of between 2mm - 5mm as per BS 7533 to cater for product alignment (butt jointing should be avoided).

Jointing Sand

AG recommends that silver and slate coloured products are jointed with AG's Granite Sand.

Colour blending

AG recommends that products are blended from 3 packs from alternate sides using full vertical sections.

Please contact our Technical Specification Department for further details.

ADVICE + GUIDANCE

For advice and guidance on ordering, installation, good site practice, etc. visit our website:
www.ag.uk.com/advice+guidance

For maintenance guidance and health and safety advice visit our website:
www.ag.uk.com/maintenance



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic when used as part of a bound system




Trolley Friendly



Abrasion Resistant

PEDESTALS

Pedestal systems are designed to support paving products on roof terraces, roof gardens, platforms and other raised areas. They resolve an array of design issues, from protecting waterproof membranes, to disguising exposed surfaces, to providing a usable roof deck. Pedestals are available in heights up to approximately 600mm. Please contact our Technical Specification Department to discuss your plans.




Information for a specific colour / depth is available on request from our Technical Specification Department

MANUFACTURING

TerraPave® flags are manufactured from specially selected granite and other natural aggregates. Their exceptional appearance is achieved by using the most up-to-date manufacturing and finishing equipment.
 PLANT OF MANUFACTURE: Made at our Toome production plant.

CERTIFICATION

BES 6001 Responsible Sourcing of Concrete Products (Rating: Very Good)
ISO 9001 Quality Management.
ISO 14001 Environmental Management.
ISO 45001 Occupational Health and Safety Management.
CE Marking Download our Declaration of Performance (DOP) data at: www.ag.uk.com/resources



TerraPave®

premium reconstituted granite aggregate flagstones



DEPTHS



40 | 50
70
Millimetres

FINISH



Ground



400 x 400mm

450 x 450mm

600 x 400mm

TerraPave®
Stock Information

STOCK INFORMATION

Standard product depth	Size (mm)	In Stock	Available Colours (in both finishes)	m ² per pack	Units per m ²	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler	Packs units per lorry
40mm	400 x 400	Yes	Rimini Ground	19.2	6.25	120	15.4	1.84	9	15
		MTO	Verona Ground							
	600 x 400	Yes	Rimini Ground	19.2	4.16	80	23	1.84	9	15
		MTO	Verona Ground							
50mm	400 x 400	MTO	Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground	15.36	6.25	96	19.2	1.843	9	13 / 15
			Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground							
	450 x 450	MTO	Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground	14.58	4.94	72	23.42	1.686	9	13 / 15
			Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground							
	600 x 400	MTO	Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground	15.36	4.16	64	28.8	1.843	9	13 / 15
			Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground							
70mm	400 x 400	MTO	Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground	10.56	6.25	66	26.9	1.775	9	13 / 15
			Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground							
	450 x 450	MTO	Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground	10.94	4.94	54	32.8	1.776	9	13 / 15
			Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground							
	600 x 400	MTO	Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground	10.56	4.16	44	40.3	1.773	9	13 / 15
			Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Sorrento Ground / Genoa Ground / Como Ground / Tuscany Ground							

Fibre reinforcement can now be specified on a MTO basis for the TerraPave® range - contact our Technical Specification Department for more information. Information for a specific colour / depth is available on request from our Technical Specification Department.

MTO: Made To Order (minimum order quantities is 600m² with a lead time of 6-8 weeks per colour / size. Orders below these quantities should be priced on application).

Enduur 1

Enhanced surface colour and reduced efflorescence.

Enhanced mix which increases strength, resistance to wear and tear, longevity and vibrance.

70% less embodied carbon per % of cement replaced.

Helps prevent moss and algae growth and deep staining.



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic when used as part of a bound system



Trolley Friendly



Abrasion Resistant

