


COVER DOURO

B125









Ref	Model	A1 x A2	O1 x O2	H	Class
920112	400	400x400	300x300	30	B125
920113	500	500x500	400x400	35	B125
920114	600	600x600	500x500	35	B125
920115	700	700x700	600x600	45	B125
920116	800	800x800	700×700	45	B125

900x900

FEATURES:

920117

• Cover in spheroidal graphite cast iron (ductile), according to EN-GJS-500-7, EN 1563;

800x800

45

B125

According to EN 124-2:2015, load class B125;

900

- Hydraulic seal to prevent the passage of odors;
- Fitted with two handles for easy lifting of the lid;
- · Surface non-slip relief;
- · Optimized hoop for laying in the surrounding concrete;
- · Black paint for corrosion protection.

DESCRIPTION

Square closing device in spheroidal graphite casting according to EN 1563 (EN-GJS-500-7).

This device is standardized for class B125, Group 2 of EN 124-2:2015. It is suitable for application on sidewalks, pedestrian zones, comparable areas, car parks for light vehicles, among others.

The rim is fitted with a hydraulic seal to prevent the passage of odors and the cover has non-slip surface relief and black paint against corrosion.

This device is available in a comprehensive range of sizes up to 900x900mm.

DRAWINGS

